



CD/K/721:2010
ICS 67.120.10

EAST AFRICAN STANDARD

Meat and meat products — Determination of free fat content

EAST AFRICAN COMMUNITY

Foreword

Development of the East African Standards has been necessitated by the need for harmonizing requirements governing quality of products and services in East Africa. It is envisaged that through harmonized standardization, trade barriers which are encountered when goods and services are exchanged within the Community will be removed.

In order to meet the above objectives, the EAC Partner States have enacted an East African Standardization, Quality Assurance, Metrology and Test Act, 2006 (EAC SQMT Act, 2006) to make provisions for ensuring standardization, quality assurance, metrology and testing of products produced or originating in a third country and traded in the Community in order to facilitate industrial development and trade as well as helping to protect the health and safety of society and the environment in the Community.

East African Standards are formulated in accordance with the procedures established by the East African Standards Committee. The East African Standards Committee is established under the provisions of Article 4 of the EAC SQMT Act, 2006. The Committee is composed of representatives of the National Standards Bodies in Partner States, together with the representatives from the private sectors and consumer organizations. Draft East African Standards are circulated to stakeholders through the National Standards Bodies in the Partner States. The comments received are discussed and incorporated before finalization of standards, in accordance with the procedures of the Community.

Article 15(1) of the EAC SQMT Act, 2006 provides that "Within six months of the declaration of an East African Standard, the Partner States shall adopt, without deviation from the approved text of the standard, the East African Standard as a national standard and withdraw any existing national standard with similar scope and purpose".

East African Standards are subject to review, to keep pace with technological advances. Users of the East African Standards are therefore expected to ensure that they always have the latest versions of the standards they are implementing.

© East African Community 2010 — All rights reserved*

East African Community

P O Box 1096

Arusha

Tanzania

Tel: 255 27 2504253/8

Fax: 255-27-2504481/2504255

E-Mail: eac@eachq.org

Web: www.each.int

Introduction

In the preparation of this East African Standard, the following sources were consulted extensively:

ISO 1444:1996, *Meat and meat products — Determination of free fat content*

Codex Alimentarius website: http://www.codexalimentarius.net/mrls/pestdes/jsp/pest_q-e.jsp

USDA Foreign Agricultural Service website: <http://www.mrlatabase.com>

USDA Agricultural Marketing Service website: <http://www.ams.usda.gov/AMSV1.0/Standards>

USDA Plant Inspectorate Service website: http://www.aphis.usda.gov/import_export/plants

European Union: http://ec.europa.eu/sanco_pesticides/public

Assistance derived from these sources is hereby acknowledged.

Draft for comments only — Not to be cited as East African Standard

INTERNATIONAL
STANDARD

ISO
1444

Second edition
1996-04-01

**Meat and meat products — Determination
of free fat content**

*Viandes et produits à base de viande — Détermination de la teneur en
matière grasse libre*



Reference number
ISO 1444:1996(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 1444 was prepared by Technical Committee ISO/TC 34, *Agricultural food products*, Subcommittee SC 6, *Meat and meat products*.

This second edition cancels and replaces the first edition (ISO 1444:1973), which has been technically revised.

Annex A of this International Standard is for information only.

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Meat and meat products — Determination of free fat content

1 Scope

This International Standard specifies a method for the determination of the free fat content of meat and meat products by means of extraction.

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 1442:1996¹⁾, *Meat and meat products — Determination of moisture content (Reference method)*.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 free fat content of meat and meat products:

Mass of the fat extracted under the conditions specified in this International Standard divided by the mass of the test portion. The free fat content is expressed as a percentage by mass.

3.2 test result: The value of a characteristic obtained by carrying out a specified test method.

[ISO 5725-1]

4 Principle

Extraction, by means of *n*-hexane or light petroleum, of the dried residue obtained in accordance with the method of determination of the moisture content specified in ISO 1442. Removal of the solvent by evaporation, then drying and weighing of the extract.

5 Reagent and material

5.1 Extraction solvent, *n*-hexane or, alternatively, light petroleum distilling between 40 °C and 60 °C, and having a bromine value less than 1. For either solvent, the residue on complete evaporation shall not exceed 0,002 g per 100 ml.

5.2 Boiling-chips

6 Apparatus

Usual laboratory apparatus and, in particular, the following:

6.1 Homogenizing equipment, mechanical or electrical, capable of homogenizing the test sample. This includes a high-speed rotational cutter, or a mincer fitted with a plate with holes not exceeding 4,5 mm in diameter.

6.2 Extraction thimble, made of filter paper and defatted.

6.3 Cotton wool, defatted.

1) To be published. (Revision of ISO 1442:1973)

6.4 Extraction apparatus, continuous or semi-continuous, for example the Soxhlet type.

NOTE 1 Instead of the classical Soxhlet technique, the extraction procedure may also be performed with extraction systems capable of simultaneous extraction of a number of samples, such as Soxtec or other similar automated instruments.

6.5 Sand bath or water bath, electrically heated, or similar suitable apparatus.

6.6 Drying oven, electrically heated, capable of being maintained at $103\text{ °C} \pm 2\text{ °C}$.

6.7 Desiccator, containing an efficient desiccant, e.g. silica gel.

6.8 Analytical balance, capable of weighing to an accuracy of $\pm 0,001\text{ g}$.

7 Sampling

It is important that the laboratory receive a sample which is truly representative and has not been damaged or changed during transport or storage.

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 3100-1.

The mass of the laboratory sample shall be not less than 200 g.

Store the sample in such a way that deterioration and change in its composition are prevented.

8 Preparation of test sample

8.1 Homogenize the test sample with the appropriate equipment (6.1). Take care that the temperature of the sample material does not rise above 25 °C . If a mincer is used, pass the sample at least twice through the equipment.

8.2 Fill a suitable airtight container with the prepared sample. Close the container and store in such way that deterioration and change in composition are prevented. Analyse the sample as soon as practicable, but always within 24 h of homogenization.

9 Procedure

NOTE 2 If it is required to check whether the repeatability requirement is met, carry out two single determinations in accordance with 9.1 and 9.2 under repeatability conditions.

9.1 Test portion

Take a known mass of 5 g to 8 g, weighed to the nearest 0,001 g (m_0) of the prepared sample and dry it by the procedure specified in ISO 1442. If desired, the dried test portion from the determination of moisture content may be used for the determination of free fat.

For reliable measurements, the lowest level of fat present in the test portion should be 0,05 g.

9.2 Determination

Dry the flask of the extraction apparatus (6.4), containing some boiling-chips (5.2), for 1 h in the drying oven (6.6) set at 103 °C . Allow the flask to cool to room temperature in the desiccator (6.7) and weigh to the nearest 0,001 g (m_1).

Transfer the dried test portion (9.1) quantitatively from the dish to the extraction thimble (6.2). Remove the last traces of the dried test portion from the dish, using cotton wool (6.3) moistened with the extraction solvent (5.1), and also transfer this cotton wool to the thimble. Place the thimble in the extraction tube of the apparatus. Pour the extraction solvent into the flask of the extraction apparatus; the amount of solvent shall be at least one and a half to two times the capacity of the extraction tube of the apparatus. Fit the flask to the extraction apparatus. Heat the flask for at least 6 h on the sand bath or water bath (6.5), according to the extraction rate and the apparatus used.

When a Soxtec or other similar automatic procedure is used, the heating period shall be at least 2 h.

After extraction, take the flask containing the liquid from the extraction apparatus and distil off the solvent using, for example, the sand bath or water bath. Evaporate the last traces of solvent using air blowing if desired.

Dry the flask for 1 h in the oven (6.6) set at 103 °C and, after allowing it to cool to room temperature in the desiccator (6.7), weigh to the nearest 0,001 g. Repeat the operations of heating, cooling and weighing until the results of two successive weighings, separated by 1 h of heating, do not differ by more than 0,1 % of the mass of the test portion (m_2).

Verify completion of the extraction by taking a second extraction flask and extracting for a further period of 1 h with a fresh portion of the solvent. The increase in mass shall not exceed 0,1 % of the test portion.

10 Calculation

Calculate the free fat content, w_f , as a percentage by mass, using the following equation:

$$w_f = \frac{(m_2 - m_1)}{m_0} \times 100\%$$

where

- m_0 is the mass, in grams, of the test portion taken for drying;
- m_1 is the mass, in grams, of the extraction flask with boiling chips;
- m_2 is the mass, in grams, of the flask and boiling chips with the fat, after drying.

Report the result rounded to one decimal place.

11 Precision

The precision of the method has been established by an interlaboratory test (see reference [4]), carried out in accordance with ISO 5725²⁾. For the values obtained for the repeatability limit, r , and the reproducibility limit, R , a probability level of 95 % holds.

11.1 Repeatability

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, should not be greater than the repeatability limit r as calculated using the following equation:

$$r = -0,05 + 0,06 \bar{w}_f$$

where \bar{w}_f is the mean of the two test results, expressed as a percentage by mass.

11.2 Reproducibility

The absolute difference between two single test results, obtained using the same method on identical test material in different laboratories with different operators using different equipment, should not be greater than the reproducibility limit R as calculated using the following equation:

$$R = 0,04 + 0,06 \bar{w}_f$$

where \bar{w}_f is the mean of the two test results, expressed as a percentage by mass.

12 Test report

The test report shall specify:

- the method in accordance with which sampling was carried out, if known;
- the method used;
- the test result(s) obtained; and
- if the repeatability has been checked, the final quoted result obtained.

It shall also mention all operating details not specified in this International Standard, or regarded as optional, together with details of any incidents which may have influenced the test result(s).

The test report shall include all information necessary for the complete identification of the sample.

2) ISO 5725:1986 was used to obtain the precision data. This has now been cancelled and replaced by ISO 5725-1:1994 and subsequent parts.

Annex A

(informative)

Bibliography

- [1] ISO 3100-1:1991, *Meat and meat products — Sampling and preparation of test samples — Part 1: Sampling.*
- [2] ISO 5725:1986, *Precision of test methods — Determination of repeatability and reproducibility for a standard test method by inter-laboratory tests.*
- [3] ISO 5725-1:1994, *Accuracy (trueness and precision) of measurement methods and results — Part 1: General principles and definitions.*
- [4] FOSTER, M.L. and SHARON, E.G. Soxtec fat analyzer for determination of total fat in meat: Collaborative Study. *J. Assoc. Off. Anal. Chem.*, **75**, 1992, pp. 288-292.

This page intentionally left blank

ICS 67.120.10

Descriptors: agricultural products, animal products, food products, meat, meat products, chemical analysis, determination of content, fats, extraction methods.

Price based on 4 pages

Draft for comments only — Not to be cited as East African Standard